



Support
customized UI



QR code
payment linux POS



Super fast
transaction



Local audio
guide feature



TRENDIT T3

RTOS POS Terminal





Specifications

	Operating System	RTOS		Camera	0.3MP(Optional)
	Processor	High performance security CPU		Printer	High Speed thermal printer Paper roll:58*40mm
	Memory	320KB RAM+4MB Flash, 320KB RAM+8MB Flash, 320KB RAM+16MB Flash		Battery	3.7V/2500mAh
	Magstripe Cards	Two-way swipe,three tracks(track1,2,3)		Adapter	Input:AC 100 - 240V 50Hz/60Hz Output:DC 5V/1A
	Chip & PIN	PBOC,EMV,ISO 7816		Dimensions	172*82*60mm
	Contactless Cards	QPBOC,EMV,ISO 14443,Mifare,Felica		Weight	360g(Including battery)
	Communication	2G, 2G/4G(Optional)		Operating Temperature	-10°C~50°C
	WiFi	2.4G(Optional)		Storage Temperature	-20°C~70°C
	Bluetooth	/		Relative Humidity	5%~95%(Non-Condensing)
	Positioning	AGPS		SIM/SAM	2*SIM+1*PSAM(Optional)
	Display	2.4" TFT,320*240 Pixels,Electronic Signature Capture		Keys	10*Numerical Key,1*Power Key,6*Function key
	Audio	1*Speaker		Ports	Type-C
	Certifications	EMV Contact L1&L2, EMV Contactless L1, Mastercard PayPass, VISA PayWave, UPI qUICS, PCI PTS 6.0, CE,RoHs,TQM			

Shenzhen Trendit Technology Co., Ltd.

 sales@trenditen.com  www.trenditen.com

 30F, 1A Building International Innovation Valley, Dashi 1st Road,
Xili Street, Nanshan District, Shenzhen City, Guangdong Province, China

You can follow us on these platforms!



Linkedin



Instagram



Twitter



Facebook